

Supercritical fluids technology in bioprocess industries: A review

Kianoush Khosravi Darani*, Mohammad Reza Mozafari

Received: 10 October 2009 / Received in revised form: 30 January 2010, Accepted: 30 January 2010, Published online: 10 March 2010
© Sevas Educational Society 2008

Abstract

This article reviews the fundamentals of supercritical fluid (SCF) science and moves on to the biotechnological applications of them e.g. removal of biostatic agents from fermentation broths, SCF disruption of microorganisms, destruction of industrial waste, the gas-antisolvent crystallization and micron-size particle formation. Also gaining ground is enzymatic catalysis in supercritical carbon dioxide (SC-CO₂), which offers the possibility of integrated synthesis product recovery processes. The paper is structured as follows: first, the effects of dense SC-CO₂ on the extraction of biomaterials and disruption of cells are thoroughly reported and discussed. Then the application of SC-CO₂ in particle formation and modifications of biopolymers and enzymes are described. In general, the article is focused on potential bio-industrial applications and future research needs of the SCF technology.

Keywords: Biotechnology, Supercritical Fluids (SCF), disruption, inactivation, extraction, downstream, particle formation

Introduction

In recent years, supercritical fluids (SCFs) have been of interest in the biotechnological processes (Williams et al 2002). They provide solutions to drastic problems related to bacterial (Dillow et al. 1999; Enomoto et al. 1997; Spilimbergo et al. 2003), enzyme (Hong and Pyun 2001), viral (Fages et al. 1998) and yeast inactivation (Hashizume et al. 1995), as well as permeabilization (Aaltonen and Rantakyla 1991; Mesiano et al. 1999) and extraction of fermentation products (Bruno et al. 1993; Cocks et al. 1995; Cygnarowicz-Provost et al. 1999; Hampson and Ashby 1999; Isenschmid et al.

1995; Saykhedkar and Singhal 2004; Shishikura et al. 1992). Application of SCF is inexpensive and non injurious to the enzymes (Lin et al. 1993) and proteins (Juhasz et al. 2003; Kamat et al. 1995; Zheng and Tsao 1996).

A SCF uniquely displays a wide spectrum of solvation power as its density is strongly dependent to upon temperature and pressure. Temperature change of ten of degrees or pressure changes of ten of atmosphere can change a compound's solubility in a SCF by an order of magnitude or more. The selectivity of nonpolar SCF can also be enhanced by addition of modifiers (entrainers or cosolvents), which are typically polar organic solvents e.g. acetone, ethanol, methanol, methylene chloride or ethyl acetate. Varying the proportion of modifier allows wide latitude in the variation of solvent power. The unusual physicochemical properties of SCF in relation to their engineering applications in polymer and waste processing have been discussed (Van-eijs et al. 1983). Advantages and disadvantages of SCE especially for the biotechnology industries have been discussed elsewhere (Van-eijs et al. 1983).

Supercritical-carbon dioxide (SC-CO₂) is the most commonly used fluid and the low critical temperature (31.1°C) and pressure (73 bar) of which make it an ideal medium for processing volatile products (Goodarznia and Eikani 1998) and other new developemnets (Marr and Gamse 2000). Non-toxicity, non-flammability as well as the selectivity of the process and the ease of recovery are the most important features (Wells and DeSimone 2001). Also SC-CO₂ was used as an antisolvent for the preparation of PHB microspheres as drug delivery systems (Bleich and Mueller 1996; Breitenbach et al. 2000; Bustami et al 2000). Applications of SCF in polymer processing have been reviewed thoroughly (Kazerian 2000). Khosravi et al. have reported the equilibrium solubility of poly(hydroxyl butyrate) (ultra-molecular weight) in SC-CO₂ at temperatures ranging from 30 to 70°C and pressures ranging from 122 to 355 bar (Khosravi-Darani et al. 2003). Khosravi et al. also have reviewed many aspects of the SCF extraction in the downstream processing of bioscience (Khosravi-Darani and Vasheghani-Farahani 2005).

The advantage of SC-CO₂ extraction fit well to those of biotechnological production processes are the mild processing temperature. CO₂ is also naturally occurring and readily available

Kianoush Khosravi Darani*

Department of Food Technology Research, National Nutrition and Food Technology Research Institute, Shaheed Beheshti Medical University, P. O. Box: 19395-4741, Tehran, I. R. Iran

*Tel: 0098 21 8800 2992, Fax: 0098 21 2237 6473
email: kiankh@yahoo.com

Mohammad Reza Mozafari

Department of Biochemistry and Molecular Biology, Monash University, Clayton Campus, Clayton, Victoria 3800, Australia

and is a by-product from the production of ammonia, ethanol, hydrogen and natural gases (Wells and DeSimone 2001). Processes that use CO₂ do not add directly to the green house effect but rather aid in the reduction of emitted CO₂. Wells et al. has discussed the technology platform that allows CO₂ to be an environmental problem solving tool for sustainable economic growth (Wells and DeSimone 2001).

SC-CO₂ introduced in a liquid decrease the overall viscosity and thus facilitates the handling of the broth and enhances mass transfer from the liquid to SC phase (Van-eijs et al. 1983). If the microorganism is inhibited by its own products, like in ethanol fermentation by yeasts and in acetone/butanol/ethanol fermentations by Clostridium, it is advantageous to extract the product in situ. If cells are resistance to SC-CO₂, the extraction may be carried out using the whole broth. The extracted fermentation broth can be recirculated to the fermenter. Other non biological applications of SCF includes extraction of organic solvents from aqueous solution, removal of chlorinated compounds from water and other water pollutants, treatment of lignocellulosic materials, recovery and purification of biological products and fractionation of cod liver oil. Other application of SCFs including non-thermal inactivation of microorganisms, dispersion media for biocatalysis and the treatment of wastes of food industries have been introduced (Khosravi-Darani 2007).

Separation of biological products from fermentation medium at high quality, efficiency and low energy cost is required. SC extraction (SCE) has some lab, pilot and industrial scale applications in downstream of fermentation. For recovery of intracellular metabolites, the cell disruption is necessary. A variety of disruption techniques have been developed (Harrison et al. 1990) and some are commercially (Tamer et al. 1998). Although the mechanical methods are favored due to economic advantages, but some times several non-mechanical methods, particularly enzymatic lysis, have attracted great attention. SCF has an important application for cell disruption which will be explained more in a separate part.

Many reviews dealt with the stability of proteins (Heremans and Smeller 1998) and enzymes (Athes et al. 1998; Degraeve and Lemay 1997; Degraeve et al. 1996; Knutson et al. 1999; Mozhaev et al. 1994) as a function of pressure. The use of hyperthermophilic enzymes (Noel Marie et al. 2000) and the characterization of deep-sea microorganisms have been also reviewed (Adams and Kelly 1998). Studies have been done to explain the properties of thermozyms.

Product recovery

Complexity of product recovery from a fermentation broth is more than chemical processes, due to product concentration, broth viscosity and biomaterial properties. SCE may provide solutions to some special limitations e.g. low product concentration. SCE by CO₂ can be carried out at fermentation temperature thus avoiding possible thermal damage of the product and saving energy costs. Table I shows a list of extracted bioproducts from fermentation. Application of SCFs in extraction of biomaterials from biomass has been widely reviewed (Khosravi-Darani and Vasheghani-Farahani 2005) and classified as following: post fermentation extraction of products; In situ extraction from the biomass of microbial fermentation; Fractionation of cellular biomass; Removal of biostatic agent from fermentation broth. It has been reported that furfural, a growth inhibitory byproducts was successfully removed during fermentation of Clostridium on sugars by introducing liquefied CO₂ into the aqueous solution at room temperature and 5.9 MPa. Such an approach was explored with several SCF including ethane, CO₂, Xe, and halogenated refrigerants during fermentations

of *Propionibacterium freudenreichii* and *E. coli* (Tomasko and Chon 1997). Refrigerant 13 (CClF₃) or R116 (CF₃CF₃) did not affect the growth of broth *P. freudenreichii* and *E. coli*. Reverse micelle formation is presented as a new strategy for improving the extraction of polar species with SC-CO₂. The addition of a reverse-micelle forming reagent prior to SFE accelerates the quantitative extraction of the analyte. (Jimenez-Carmona et al. 1998).

Table 1: Application of SCF in downstream of biotechnological processes

Product	Microorganism	Process Condition	Reference
Ethanol	<i>Saccharomyces cerevisiae</i>	Pilot scale, continuous countercur rent	Van-eijs 1983
Acetic/Propanoic/Butanoic acid	<i>Clostridium thermoaceticum</i>	Laboratory scale, batch	Van-eijs 1983
Aceton/Butanol/Ethanol	<i>Clostridium acetobutylicum</i>	Pilot scale, batch	Van-eijs 1983
Substituted thiophenes	<i>Tagetes patula</i> cells	-	Van-eijs 1983
Complex lipids: (acylglycerols, phosphoglycerides, sphingolipids, waxes)	Animal source material	-	Kamarei 1983
Simple lipids (terpenes, pigments, steroids, sterols, prostaglandins)	Animal source material	-	Kamarei 1983
Glycolipids, lipoproteins, cell membrane supramolecular complexes	Animal source material	-	Kamarei 1983

Detecting the presence of a microorganism

Another interesting application of SCF in biotechnology is detecting the presence of a microorganism in a sample. In this strategy, nucleic acid of pathogen will isolate after exposure to SCF. Then, detecting of contamination to a particular sequence will be conducted by hybridization and PCR method (Nivens and Applegate 1996). Importantly, this method can be used the presence of pathogenic microorganisms in water supplies. A major advantage of this method is its application for all microorganisms (preferably, a bacterium; alternatively, a protozoan, parasite, or virus.). Even if partial or preferential lysis occurs, the extracted DNA can be representative of contamination in sample, rapidly. DNA appears very resistance to hydrostatic pressure. Structural integrity of calf thymus or salmon sperm DNA remained unchanged when pressures of up to 10000 at were applied for 60 min at 25-40°C.

A SCF extraction procedure and a chromatographic separation/detection method were developed for the detection of earth-based microorganisms. After microbes in a sand or soil sample were hydrolyzed in a diluted NH₄OH/acetone solution, several redox compounds could be effectively extracted from bacteria (trimethylamine- SC-CO₂ at 35°C and 300 at). The analytical results demonstrated the feasibility of using the reported techniques to detect the chemical signature of life in barren desert sand samples (Lang et al. 2002).

Inactivation of microorganisms

Application of supercritical is a promising alternative method for the pasteurization and sterilization of foodstuff (particularly in the liquid phase), as well as chemically, thermally and hydrolytically

sensitive materials in biomedical applications. The development of this effective alternative method and its lethal action of high hydrostatic pressure CO₂ on microorganisms, has been reviewed by Khosravi (2007).

Cell disruption

The potential use of the intracellular storage products such as poly(β -hydroxybutyrate) (PHB) and recombinant metabolites have led to the increased interest in efficient and cost effective cell disruption to enable the recovery of intracellular microbial products in intact form (Lee et al. 1979). Mechanical disruption methods are favored due to economic advantages. Homogenization after a suitable pretreatment is a proven recovery method, although only relatively dilute biomass slurries can be satisfactorily processed (Tamer et al. 1998). Harrison has shown that chemical (addition of an anionic detergent and monovalent cation) or lysozyme pretreatment can weaken the cell wall sufficiently to decrease energy consumption and allows for operation at lower pressures or fewer passes with the homogenizer (Harrison et al. 1990). Also bead mill disruption is recommended for PHB recovery due to low power consumption and robustness (Heremans and Smeller 1998). In this method the agitation speed will affect the amount of energy consumption but when rotation was increased to a critical level, only a marginal increase was found with the excess energy being converted to heat (Schutte et al. 1983).

The cell disruption operation affects the physical properties of the cell slurry such as viscosity (Mosqueira et al. 1981), density, particle size, and settle ability of suspension (Lee et al. 1979). The necessity of harvesting the producing cells, in order subsequently to extract an internal constituent, is a major economic disadvantage, and, in part, results in the present preoccupation with the manufacture of products of very high value (Chisti and Moo-Young 1986). Because of the high capital and operating costs for large-scale isolation of intracellular products and the requirement of sizeable teams of scientists and technical staff to obtain meaningful biochemical engineering data, few studies on this subject have been published (Chisti and Moo-Young 1986).

Application of SCF in cell disruption (SC disruption) has been confined to yeasts (Castor and Hong 1995, Lin et al. 1991; Nakamura et al. 1994) and a few bacteria (Foster et al. 1962; Fraser 1951; Juhasz et al. 2003). The process involves a sudden release of the applied SC-CO₂ pressure that will result in its penetration into the cells. After expansion of gas within the cells, flash discharge of

pressure forces the cell wall and causes cell disruption. The technique is relatively simple and can easily be scaled up (Juhasz et al. 2003). Also, the cells are exposed to minimal shear forces and there is no heat generation, which would otherwise affect the yield of temperature sensitive and labile material recovery adversely.

Disruption of microbial cells by sequential pressurization and explosive decompression was first reported by Fraser (Fraser 1951) and then developed by several researchers to recover intracellular enzymes and recombinant-DNA proteins (Castor et al. 1996; Foster et al. 1962; Lin and Chen 1994; Lin et al. 1991; 1992; 1993; Nakamura et al. 1994). Several studies have been reported on cell inactivation by SCF (Khosravi-Darani and Vasheghani-Farahani 2005).

A technique to exploit SC-CO₂ disruption of *R. eutropha* cells has been developed (Hejazi et al. 2003). The effects of different variables such as exposure time, pressure, temperature and volume of methanol (as a modifier) on SC disruption of suspension of bacterium were investigated. Khosravi et al. extended this work to obtain maximum recovery with minimum energy consumption (Khosravi-Darani et al. 2004). The variables affecting cell disruption such as drying strategy, type of modifier and cultivation time, as well as operating pressure, temperature and repeated release of supercritical-CO₂ pressure have been studied. Also a series of pretreatment experiments were arranged to alter cell wall strength prior to disruption and to minimize repetition of pressure release. The effect of cultivation time on the PHB recovery was also studied. On the result of this study, the optimum conditions for the recovery of PHB using SC-CO₂ were 200 bar of pressure, 30°C temperature and 1% (v/v) of toluene with two repeated release of SC-CO₂ pressure. Pretreatment with a minimum of 0.4% (w/w) NaOH was necessary to enable complete disruption with two repetitions of pressure release. Salt pretreatment was less effective; however, disruption was improved by the application of alkaline shock (Khosravi-Darani et al. 2004).

It has been reported that young cells are more susceptible to CO₂ treatment than mature ones due to synthesis of new proteins, which protect cells against a variety of adverse conditions such as high temperature, oxidative stress, high salt concentration and pressure (Kashket 1987; Mackey et al. 1995). Similar results have been reported for maximum efficiency in yeast disruption requiring log phase cells (Castor and Hong 1995). Consequently, biomass produced after 30 h cultivation was used to save energy and time for PHB recovery (Khosravi-Darani et al. 2004).

Table 2: Application of SCF for disruption of different cells

Microorganism	SCF	Disruption Condition			Criteria of disruption	Reference
		P(atm)	T(°C)	Time(h)		
Yeasts, bacteria, water plant, fungi,	N ₂ , air,	80-200	n r ^a	n r	Release of Protein, nucleic acids, enzymes, physiological active substances	Grigorian et al. 1982
<i>Saccharomyces cerevisiae</i>	CO ₂	70-215	25-35	0-10	Release of Protein	Lin et al. 1992
<i>Saccharomyces cerevisiae</i>	CO ₂	34-340	10-85	1-15	Release of Protein	Lin and Chen 1994
<i>E. coli</i>	N ₂	34-61	37-38	0.08	Agar plate count & direct observation by electron microscopy	Fraser 1951
	N ₂ O	17-51				
	Ar	34-61				
	CO ₂	34				
<i>Serratia marcescens</i>	N ₂	51-118	n r	n r	direct observation by electron Microscopic	Foster et al. 1962
<i>Saccharomyces cerevisiae</i>	N ₂ , CO ₂	40 at	40	3	Agar plate count/ direct observation by electron microscopy	Nakamura et al. 1994
<i>Saccharomyces cerevisiae</i> , <i>E. coli</i> ,	N ₂ , N ₂ O,	Near	Near	n.r	Released protein and nucleic acid	Castor and Hong 1995
<i>Bacillus subtilis</i>	CO ₂	critical	critical			
<i>Ralstonia eutropha</i>	CO ₂	SC	SC	0.33	Released protein and Poly(hydroxybutyrate)	Khosravi et al. 2004

^a not reported

In another report *Saccharomyces cerevisiae* and the spore cells of *Bacillus megaterium* were selected as model microorganisms and the lethal effect of pressurization and subsequent flash decompression treatments with CO₂, N₂O, N₂ or Ar under various conditions of pressure, temperature, and time were examined. In all reports, during pressurization with CO₂, the absorbed gas may cause the inactivation of key enzymes related to the essential metabolic process, probably due to decreased pH value inside the cells and/or the solubilization of intracellular substances such as hydrophobic compounds in the cell wall and cytoplasmic membrane (Juhász et al. 2003). Also cells may be broken by the pressurization process, and not in the decompression stage. Yeasts predominantly killed by SCF due to physiological damage of and mechanical rupture. Different experimental data have been also reported to support the lethal action of rapid discharge by the explosive decompression system, as already mentioned (Enomoto et al. 1997; Fraser 1951; Hejazi et al. 2003; Khosravi-Darani et al. 2004). It has reported that higher decompression rates up to 48 at/min could lead to about a two-order-higher reduction of the remaining cells when 10⁹ cells/mL of yeast had been treated with CO₂ at 40 at and 40 °C for 4 h (Enomoto et al. 1997). Table II shows some of the reported disruption process using flash discharge of SCF.

Enzymatic pretreatment of cells (e. g. beta-glucuronidase, lysozyme, glucanase) is another effective means to reduce the resistance of microorganisms to disruption (Lin et al. 1992). Preferably the enzyme and protein in the cells remains active and native state in the ruptured cell suspension (Lin and Chen 1994).

In some reports continuous disruption of microorganisms by SCF have been reported (Kashket 1987). To effect disruption of yeast, bacteria and fungi, a suspension of cells is presaturated with a compressed gas and then passed through one or more disintegration units containing a plate valve seat and valve member urged toward each other. The disruption unit can be attached to a mechanical vibrator-shaker. There were two thick wall vessels (mixing part) in the inlet of this unit (to effect intermixing of the suspension) and a homogenizing vessel (to maintain the suspension under pressure of 100-120 at). The cell walls are intensively disrupted when the suspension is passed through a throttling slit formed between the valve seat and valve member, due to the internal pressure.

The variables which must be studied in order to obtain efficient cell breakage include temperature, pressure, exposure time, moisture content of the cells, initial rate for gas desorption, microbial age or shape, number of flash discharge of pressure, vessel capacity and shape, as well as fermentation conditions e. g. strain of microorganism, media composition and carbon source (Khosravi-Darani et al. 2004; Hopkins 1991).

Biochemical reactions in SCF

The solubility of substrate in SCF, the stability of proteins (Athes et al. 1998) and enzymes in SCF have been widely studied (Adams and Kelly 1998; Jimenez-Carmona and Luque de Castro 1998; Mozhaev et al. 1994; 1996; Nakamura 1990; Noel Marie et al. 2000). Among the enzymatic reactions in SCF, the use of lipase shows most commercial promise. A SC-CO₂/H₂O mixture may be used as a reaction medium for either hydrolytic or synthetic reactions catalyzed by lipase and other appropriate by hydrolases (Giebauf et al. 1999). In continuous reaction of acidolysis of triolein with stearic acid, the constants of the reaction and mass transfer such as rate constant, solubility, effective diffusivity, mixing diffusivity and mass transfer coefficient depend on temperature, pressure and flow velocity (Nakamura 1990).

Immobilized *Candida antarctica* lipase B was successfully used as catalyst to synthesize butyl butyrate from butyl vinyl ester and 1-butanol in SC-CO₂ with excellent results. A clear enhancement in the synthetic activity and selectivity was observed with the decrease in fluid density for both liquids and SC-CO₂ media. However, all SC conditions assayed enhanced up 84-folds respect to the organic solvents the synthetic activity of the lipase-membrane derivative. For the best SC conditions (60°C, 8 MPa), the enzymatic membrane was assayed by repetitive operational cycles of 6 h/day, showing a 360 cycles half-life time in their synthetic activity (Lozano et al. 2004).

Also a commercial solution of free *Candida antarctica* lipase B (Novozyme 525L) has been immobilized by adsorption onto 12 different silica supports modified with specific side chains (e.g. alkyl, amino, carboxylic, nitrile, etc.). The immobilized derivatives were assayed for the kinetic resolution of *rac*-1-phenylethanol in both ionic liquid/hexane and ionic liquid/SC-CO₂ biphasic media. The best results were obtained for the supports modified with non-functionalized alkyl chains and when the in water activity increased from 0.33 to 0.90 (e.g. the CALB/butyl-silica activity was enhanced up to five times). Immobilized derivatives coated with ionic liquids clearly improved their synthetic activity in SC-CO₂ by up to six times with respect to the hexane medium, which agrees with the "philicity" between alkyl chain lengths of both the silica support and the cation of ionic liquid (Lozano et al. 2007).

Pseudomonas cepacea lipase (PCL) was used to catalyze the transesterification reaction between 1-phenylethanol and vinyl acetate in SC-CO₂. The effect of SC-CO₂ pressure on the catalytic efficiency of PCL at a constant temperature was evaluated. The catalytic efficiency of enzyme enhanced by increasing pressure of the reaction medium. Moreover SC sulphur hexafluoride (SCSF6) was used as reaction medium. Results showed high stability of the enzyme in this SC medium and kinetic curve reported point out increased reaction rates in comparison to those achieved in SC-CO₂ (Celia et al. 2005).

Proteinase from *Carica papaya* latex was tested on its thermal stability at atmospheric pressure and in SC-CO₂, nearcritical propane and dimethyl-ether. In SC-CO₂ at 300 bar thermal activation of the examined proteinase was improved in the comparison to atmospheric pressure. Activity of the examined proteinase decreased in propane and dimethyl-ether (300 bar). Addition of water in the system increased activity of proteinase from *C. papaya*, which was incubated in SC-CO₂ for 24 h. Optimum amount of water was found to be between 0.5 and 0.7 g/L (Habulin et al. 2005).

Isoamyl acetate was synthesized from isoamyl alcohol in SC-CO₂ by enzymatic catalysis. Among several reactants, including acetic acid and two different acetates, acetic anhydride gave best yields. Two different immobilized lipases (Novozym 435 from *Candida antarctica* and Lipozyme RM-IM from *Rhizomucor miehei*) as biocatalysts were compared. An esterification extent of 100% was obtained in continuous operation using acetic anhydride as acyl donor and Novozym 435 as enzyme. The effect of substrates load in the solvent was investigated. Operating at a CO₂/substrates molar ratio below 7.0, the conversion of alcohol decreased, due to an inhibitory effect of high concentration of acetic anhydride or acetic acid on enzyme. Pressure in the range of 8–30 MPa showed no effect on this reaction, while an increase in temperature (over 313 K) led to lower production of isoamyl acetate (Romero et al. 2005). In another report, cocoa beans had been subjected to various pod storage periods prior to fermentation were analysed for pyrazines. SC-CO₂ extraction was used for the extraction of the compounds

and quantitative and qualitative analyses of the extracts were achieved by using gas chromatography and gas chromatography-mass spectrometry. Pyrazine compounds identified in the extract included pyrazine, 2-methylpyrazine, 2,3-dimethylpyrazine, 2,6-dimethylpyrazine, trimethylpyrazine and tetramethylpyrazine. The concentration of pyrazine compounds in the cocoa beans, in particular 2,6-dimethylpyrazine and tetramethylpyrazine were found to be largely proportional to pod storage period (Sanagi et al. 1997).

Acidic or basic species can partition into the microenvironment of the enzyme molecules and adversely affect their protonation state. In present of a dilute aqueous phase, these effects may be analyzed in terms of a pH value. At low a_w , it may be more useful to think in terms of direct reaction with protein groups (Halling 1994).

Continuous method with microbubbles of SC-CO₂ was applied to enzyme inactivation in a buffer system. Alfa-amylase and acid protease were inactivated by continuous treatment with microbubbles of SC-CO₂. Inactivation efficiency of this method was affected by initial pH and the buffer action of samples (Yoshimura et al. 2002a; 2002b).

SCFs: puissant media for the modification of biopolymers

The use of SCFs as media for several types of polymer modification has been demonstrated (Yalpani 1993). Treatment of mixtures of chitosan with glucose or malto-oligosaccharides in SC-CO₂ afforded the corresponding water soluble imine-linked, branched chitosan derivatives with high degrees of conversion. Treatment of starch, maltodextrins, cellulose acetate, poly(vinyl alcohol) and paper with mixtures of SC-CO₂ and O₂ (19:1 v/v) led to the corresponding oxidized materials.

Gasification of straw

Bioconversion of lignocellulosics consists of substrate pretreatment by high pressure steam (for fractionation into cellulose, hemicellulose and lignin components), enzymatic hydrolyz, followed by fermentation of the liberated sugars to ethanol. The various technoeconomic models developed by network members were used to identify probable process schemes and determine technical "bottlenecks" (Saddler 1992).

Waste treatment

Waste treatment is one of the most important and urgent problems in environmental management around the world. SC-water oxidation has attracted attention for the treatment of industrial waste, especially toxic and refractory waste. In a study, SC-water oxidation with hydrogen peroxide was applied as the oxidant to the treatment of a model municipal solid waste containing proteins, fats, vitamins, fiber, and inorganic minerals. The effects of temperature, oxidant concentration, and reaction time on the decomposition of solid waste were investigated in a batch reactor with hydrogen peroxide over the temperature range of 673-823 K. The liquid reaction products were analyzed to determine the total organic carbon, organic acid, and ammonium ion contents. The activation energy was 97.2 kJ/mol for the reduction of total organic carbon and 130.8 kJ/mol for the reduction of ammonium ion, when analyzed by first-order kinetics (Mizuno et al. 2000).

Destruction of Industrial wastes

Several SCFs have been tested successfully on waste materials on industrial nature. For example SC-water is very reactive, corrosive, and miscible with air and oxygen. An industrial process was

describes the use of SC water to treat aqueous solutions containing organic compounds (Haas et al. 1989). A major pharmaceutical company has described the operation of a process based on this technology to treat waste generated from recombinant fermentation (Krishna et al.1986).

Particle formation

The rapid expansion of SCF is a promising new technology for particle formation and distribution of biodegradable polymeric (Debenedetti et al. 1993). Because of the extreme fragility of organic aerogels attempts are made to develop inorganic aerogels. Such microcellular polymers foams can be obtained directly by polymerization in a near critical diluent and SC drying in the same reactor vessel. The diluent is the key factor and Freon-22 is found to be superior to propane for the polymerization of poly(methyl metacrylate-co-ethane glycol-dimethacrylate) (Srinivasan and Elliott 1992).

In polymer industry, polymerization is stopped by adding a termination agent. The polymer solution is contacted with superheated steam to remove unreacted monomer and polymerization solvent (de solvent process). SC-CO₂ extraction can be alternative for the de-solvent process of polymer solutions. In fact SC-CO₂ can reduce the drying process due to its capability of complete recovery by depressurizing. In addition, SC-CO₂ can dissolve the typical polymerization solvents, *n*-hexane or toluene at higher pressures. The design of the de-solvent process requires quantitative information on the distribution of organic solvent between the polymer solution and the SC-CO₂ phase (Inomata et al. 1999).

Production of different morphologies of biocompatible polymers

SC antisolvent method has great potential for processing of pharmaceuticals (Mosqueira et al. 1981; Steckel et al. 1997) and labile compounds such as proteins (Debenedetti et al 1993; Winters et al. 1999; Yeo et al. 1994; Yeo et al. 1993) and to obtain various morphologies of biopolymers (Bleich et al. 1996; Debenedetti et al. 1993; Dixon and Johnstone 1993; Reverchon 1999; Subramanian et al. 1997), such as microspheres (Falk et al. 1997) threads, fibers, networks (Dixon and Johnstone 1993), sponges, foams, and films. One of the advantages of using SCF in polymer processing is the possibility of producing different solid shapes and structures at low temperature with a minimum amount of residual organic solvents. Also the process is environmentally safe and economic (Elvassore et al. 2001). A basic description of these techniques is reported in Bertuccio and Pallado (2000). Also SC-CO₂ has been exploited as an antisolvent for processing value added materials e.g. hyaluronic acid-based biopolymers.

Preparation of liposome

Liposomes are non-toxic (mostly) and effective in encapsulation of materials from the environment (Mortazavi et al. 2007). Several studies have indeed shown that liposomes form a basis for controlled release food processes (Mozafari and Khosravi-Darani 2007) such as for the release of enzyme involved in cheese ripening (Kheadr et al. 2003). Liposomes can be prepared in a 50-mL autoclave equipped with a variable speed agitation device. The general protocol started with the injection of predefined quantities of the solute and phospholipids to the reactor. After heating to a specified temperature, solution was pressurized to 30.0 MPa under gentle agitation. After agitation at 100 rpm for 5 minutes, the vessel was depressurized over a period of about 45 minutes. The liposomes were finally isolated and stored at 4°C under nitrogen.

Encapsulation efficiency was independent of solute concentration between 10 and 50 mg/mL and of pressure above the critical pressure. However, significant effects were observed with respect to lipid concentration, temperature and initial volume of aqueous phase (Frederiksen et al. 1997).

Manufacturing of liposome by SCF covers three separate methods including: (i) phospholipids solvation in a near critical fluid, mixture with a protein containing buffered solution (ii) decompression of solvated phospholipids prior to injection to solution, (iii) the critical fluid decompression technique in which phospholipids are first hydrated in an aqueous buffer, mixed with SCF, with the mixture being then submitted to decompression. Several parameters can improve the characteristics of the liposomes prepared with SCF ethane. Optimization studies would be necessary to examine whether liposomes of higher quality can be made using SCF technology. Also, other SCF should be tested (Frederiksen et al. 1997).

Purification of natural active copolymers

Conventional purification methods (e.g. molecular sieving, ion exchange chromatography, etc) are not specific and must be repeated or combined for highly purification. Although, (immuno) affinity-based procedures are rapid and specific; but they are expensive, and reagents from biological origin are needed. Also the interactions involved between the product and the support are often strong and imply the use of rather denaturing reagents (either for the product or the support) to attain an efficient desorption yield (Lemay 2002). SCE has introduced as a more suitable method for purification of natural products. This technique helps to remove trace impurities in the synthetic active biocopolymers from maleic anhydride and pinene (Jarzelski and Malinowski 1995).

In situ studies of protein conformation

The conformation of monomeric enzyme trypsin has been reported in SC-CO₂ (Zagrobelyny and Bright 1992). To follow in situ conformation of trypsin (as a function of CO₂ density), steady state fluorescence spectroscopy was used. Zagrobelyny showed that protein denaturation can occur during the fluid compression step and that the native trypsin is only slightly more stable (1.2 kcal/mol) than the unfolded form.

Conclusion

From the results of a number of extractions reported in literature can be concluded that by SC-CO₂ application selective extraction of several compounds from aqueous media of fermentation broth is possible. Non polar compounds can be extracted at low energy costs by this procedure. The process is cost effective due to carrying out at fermentation temperature. If whole fermentation broth put in contact with SC-CO₂, may inactivate the microorganisms. The survival rate may increase by buffering the medium and carefully controlled pressure change. These results offer the opportunity of in situ extraction of fermentation products with SC or sub critical (liquid) CO₂. Use of SCF for both the disruption and extraction simplifies the procedure, and minimizes equipment and labor needs, time, contamination and loss of yield. Indeed the entire process can be readily automated. The use of super or near critical fluids allows for easy removal of much of the solvent by depressurization. The use of SCF allows the control of extraction condition by variation of temperature, pressure or modifier solvents. By varying the choice of SCF, experimental conditions and animal source material, one may obtain lipids, proteins, nucleotides, saccharids and other desirable components or remove undesirable components.

The bactericidal effect of the CO₂ treatment on baker's yeast was found to be dramatically enhanced with increasing pressure ranging from 10 to 40 at and temperature range of 20 to 40 °C and these two factors tended to synergistically act with each other.

The finding that fermentation conditions influence the resistance of microbial cells to disruption should be further investigated. Studies of disruption kinetics and of the influence of cell morphology on kinetics of disruption are needed, and not information is available on disruption of mycelial organisms. The effects of thermal deactivation on cell properties and pre-incubation temperature on cell resistance to heat shock have received less attention. Further work is therefore required to characterize this interaction and relate it to changes in cell and broth properties.

Also cell wall of microorganisms can be weakened by a physical, chemical and/or enzymatic pretreatment, or lysogenic bacteriophage; will the enzymes remain active, native and applicable for reuse. Selection of wall-deficient mutants which are triggered to lyse by an increase in temperature, shift in pH, or the like seems attractive. Application of SCF is useful for establishment of a simple, safe and inexpensive sterilization method for heat-sensitive materials.

Biocompatible biopolymers, which have been produced by SC-CO₂ antisolvent techniques, can be used in the design of controlled delivery systems.

In the near future research development of CO₂ treatment should move to retention of vitamins and the modifications of cell enzymes and biopolymers, extraction of fermentation products, cell disruption and, in general, the effect of CO₂ processing on biotechnological materials.

SC disruption of microbial cells is comparable with a mechanical method from efficiency as well as economical points of view. Alkaline shock is recommended as a powerful pretreatment for cell wall weakening, however, especial care is necessary to ensure protection of disrupted homogenate against metabolite degradation by alkaline hydrolysis. The survey presented here clearly shows that the rapid expansion of SCFs has great potentials for application in the several industries, especially for micron sized particle formation. A major disadvantage in SFE application for biomolecules is the difficulty in measurement and prediction of their solubilities in SCF at various pressures and temperatures for process optimization. Also it is difficult to make an accurate of the solubility and separation efficiency of these compounds in SCF because the composition of the equilibrium SCF phase is easily modified shifted by both temperature and pressure on sampling. Much attention should be draw to the measurement in situ at the SC state.

References

- Aaltonen O, Rantakyla M (1991) Biocatalysis in supercritical CO₂. Chem Tech 21:240-248
- Adams MW, Kelly RM (1998) Finding and using hyperthermophilic enzymes. Trend Biotechnol 16:329-332
- Athes V, Lange R, Combes D (1998) Influence of polyols on the structural properties of Kluyveromyces lactis L-galactosidase under high hydrostatic pressure. Euro J Biochem 255:206-212
- Bertucco A, Pallado P (2000) Micronization of polysaccharide by a supercritical antisolvent techniques. pp 193-200, In: Williams JR, Clifford AA (ed) Methods in Biotechnology: Supercritical fluid methods and protocols. Vol 13, Humana Press, Totowa

- Bleich J, Mueller A (1996) Production of drug based microparticles by the use of supercritical gases with the aerosol solvent extraction system (ASES) process. *J Microencaps* 13:131-139
- Breitenbach A, Mohr D, Kissel T (2000) Biodegradable semi-crystalline comb polyesters influence the micro-sphere production by means of a supercritical fluid extraction technique. *J Ctrl Release* 63:53-68
- Bruno TJ, Castro C, Hamel JP et al (1993) Supercritical fluid extraction of biological products. pp. 303-354. In: Kennedy JF, Cabral J (ed) *Recovery Processes for Biological Materials*, John Wiley and Sons, New York
- Bustami RT, Chen HK, Dehghani F et al (2000) Generation of microparticles in proteins for aerosol delivery using high pressure modified carbon dioxide. *Pharmac Res* 17:1360-1366
- Castor TP, Chikarmane HM, Hong GT et al (1996) Methods for fraction of biological-derived materials. US Patent 5,854,064
- Castor TP, Hong GT (1995) Supercritical Fluid Disruption of and Extraction from Microbial Cells. US Patent 5,380,826
- Celia E, Cernia E, Palocci C et al (2005) Tuning *Pseudomonas cepacea* lipase (PCL) activity in supercritical fluids. *J Supercrit Fluids* 33:193-199
- Chisti Y, Moo-Young M (1986) Disruption of microbial cells for intracellular products. *Enz Microb Technol* 8:194-204
- Cocks S, Wrigley SK, Chicarelli RMI et al (1995) High-performance liquid chromatography comparison of supercritical fluid extraction and solvent extraction of microbial fermentation products. *J Chrom A* 697:115-122
- Cygnarowicz-Provost M, O'Brien DJ, Maxwell RJ et al (1999) Supercritical extraction of fungal lipids using mixed solvents: experiment and modeling. *J Supercrit Fluids* 5:24-30
- Debenedetti PG, Tom JW, Kwauk X et al (1993) Rapid expansion of supercritical solutions (RESS): fundamentals and applications. *Fluid Phase Equ* 82:311-321
- Degraeve P, Delorme P, Lemay P (1996) High hydrostatic pressure-induced deactivation of *Escherichia coli* L-galactosidase: influence of pH and temperature. *Biochim Biophys Acta* 1292:61-68
- Degraeve P, Lemay P (1997) High-pressure-induced modulation of the activity and stability of *Escherichia coli* (lacZ) L-galactosidase: potential applications. *Enz Microb Technol* 20:550-557
- Dillow AK, Dehghani F, Hrkach JS et al (1999) Bacterial inactivation by using near and supercritical carbon dioxide. *Proc Nat Acad Sci USA* 96:10344-10348
- Dixon DJ, Johnstone KP (1993) Formation of microporous polymer fibers and oriented fibrils by precipitation with a compressed fluid antisolvent. *J Appl Pol Sci* 50:1929-1942
- Elvassore N, Baggio M, Pallado P et al (2001) Production of different morphologies of biocompatible polymeric materials by supercritical CO₂ antisolvent techniques. *Biotechnol Bioeng* 73:449-457
- Enomoto A, Nakamura K, Nagai K et al (1997) Inactivation of food microorganisms by the high pressure carbon dioxide treatment with or without explosive decompression. *Biosci Biotechnol Biochem* 61:1133-1137
- Fages J, Poirier B, Barbier Y et al (1998) Viral inactivation of human bone tissue using supercritical fluid extraction. *ASAIO J* 44:289-293
- Falk R, Randolph T, Meyer JD et al (1997) Controlled release of ionic pharmaceuticals from poly (L-lactide) microspheres produced by precipitation with a compressed antisolvent. *J Control Rel* 44: 77-85
- Foster JW, Cowan RM, Maag TA (1962) Rupture of bacteria by explosive decompression. *J Bacteriol* 83:330-334
- Fraser D (1951) Bursting bacteria by release of gas pressure. *Nature* 167:33-34
- Frederiksen L, Anton K, Van-hoogevest P et al (1997) Preparation of liposomes encapsulating water-soluble compounds using supercritical carbon dioxide. *J Pharm Sci* 86:921-928
- Giebauf A, Magor W, Steinberger DJ et al (1999) A study of hydrolases stability in supercritical carbon dioxide. *Enz Microb Technol* 4:577-583
- Goodarznia I, Eikani MH (1998) Supercritical carbon dioxide extraction of essential oils: modeling and simulation. *Chem Eng Sci* 53:1387-1395
- Haas GJ, Prescott HEJ, Dudley E et al (1989) Inactivation of microorganisms by carbon dioxide under pressure. *J Food Safety* 9:253-265
- Habulin M, Primozic M, Knez Z (2005) Stability of proteinase form *Carica papaya* latex in dense gases. *J Supercrit Fluids* 33:27-34
- Halling PT (1994) Thermodynamic predictions for biocatalysis in nonconventional media: theory, tests, and recommendations for experimental design and analysis. *Enz Microb Technol* 16:178-206
- Hampson JW, Ashby RD (1999) Extraction of lipid-grown bacterial cells by supercritical fluid and organic solvent to obtain pure medium chain-length polyhydroxyalkanoates. *J Amr Oil Chem Soc* 76:1371-1374
- Harrison S, Dennis JS, Chase SA (1990) The effect of culture history on the disruption of *Alcaligenes eutrophus* by high-pressure homogenization. In: Pyle DL (ed) *Separation for Biotechnology II*, Elsevier, London
- Hashizume C, Kimura K, Hayashi R (1995) Kinetic-analysis of yeast inactivation by high-pressure treatment at low-temperatures. *Biosci Biotechnol Biochem* 59:1455-1458
- Hejazi P, Vasheghani-Farahani E, Yamini Y (2003) Supercritical disruption of *Ralstonia eutropha* for recovery of poly(hydroxybutyrate). *Biotechnol Prog* 19:15-19
- Heremans K, Smeller L (1998) Protein structure and dynamics at high pressure. *Biochim Biophys Acta* 1386:353-370
- Hong SI, Pyun YR (2001) Membrane damage and enzyme inactivation of *Lactobacillus plantarum* by high pressure CO₂ treatment. *Int J Food Microbiol* 63:19-28
- Hopekins TR (1991) Physical and chemical cell disruption for the recovery of intracellular proteins. *Bioproc Technol* 12:57-83
- Inomata H, Honma Y, Imahori M et al (1999) Fundamental study of the de-solvating polymer solutions with supercritical CO₂. *Fluid Phase Equ* 158-160:857-867
- Isenschmid A, Marison IW, Von Stockar U (1995) The influence of pressure and temperature of compressed CO₂ on the survival of yeast cells. *J Biotechnol* 39:229-237
- Jarzebski AB, Malinowski JJ (1995) Potentials and Prospects for Application of Supercritical Fluid Technology in Bioprocessing. *Proc Biochem* 30:343-352
- Jimenez-Carmona MM, Luque de Castro MD (1998) Reverse-micelle formation: a strategy for enhancing CO₂-supercritical fluid extraction of polar analytes. *Anal Chim Acta* 358:1-4
- Juhasz T, Szekely E, Simandi B et al (2003) Recovery of a recombinant thermostable endoglucanase from *E. coli* using supercritical carbon dioxide cell disruption. *Chem Biochem Eng Quart* 17:131-134
- Kamarei AR (1983) Supercritical fluid extraction of animal derived materials, USP 4749522
- Kamat SV, Beckam EJ, Russell AJ (1995) Enzyme activity in supercritical fluids, *Criti Rev Biotechnol* 15:41-71
- Kashket ER (1987) Bioenergetics of lactic acid bacteria: cytoplasmic pH and osmotolerance. *FEMS Microbiol Rev* 46:223-244
- Kazerian SG (2000) Polymer processing with supercritical fluids. *Pol Sci C* 42:78-101

- Kheadr EE, Vuilleumard JC, El-Deeb SA (2003) Impact of liposome-encapsulated enzyme cocktails on cheddar cheese ripening. *Food Res Int* 36:241-252
- Khosravi-Darani K (2007) Research Activities on Supercritical Fluid Science in Food Biotechnology. *Crit Rev Food Sci Nutrition* in press, 2010
- Khosravi-Darani K, Vasheghani-Farahani E (2005) Application of supercritical fluid extraction in biotechnology. *Crit Rev Biotechnol* 25:1-12
- Khosravi-Darani K, Vasheghani-Farahani E, Shojaosadati SA et al (2004) The effect of process variables on supercritical fluid disruption of *Ralstonia eutropha* cells for poly(hydroxybutyrate) recovery. *Biotechnol Prog* 6:1757-1765
- Khosravi-Darani K, Vasheghani-Farahani E, Yamini Y (2003) Solubility of poly(hydroxybutyrate) in supercritical carbon dioxide. *J Chem Eng Data* 48:860-863
- Knutson BL, Strobel HJ, Nokes SE, et al (1999) Effect of pressurized solvents on ethanol production by the thermophilic bacterium *Clostridium thermocellum*. *J Supercrit Fluids* 16:149-156
- Krishna G, Czerkawski JW, Breckenridge G (1986) Fermentation of various preparations of spent hops (*Humulus lupulus* L.) using the rumen simulation technique (Rusitec). *Agr Wastes* 17:99-117
- Lang Q, Cheng IF, Wai CM et al (2002) Supercritical fluid extraction and high-performance liquid chromatography-diode array-electrochemical detection of signature redox compounds from sand and soil samples. *Anal Biochem* 301:225-234
- Lee CH, Tsang SK, Urakabe R et al (1979) Disintegration of dried yeast cells and its effect on protein extractability, sedimentation property, and viscosity of the cell suspension. *Biotechnol Bioeng* 21:1-17
- Lemay P (2002) The use of high pressure for separation and production of bioactive molecules. *Biochim Biophys Acta Prot Struc Mol Enz* 1595:357-366
- Lin HM, Chan EC, Chen C et al (1991) Disintegration of yeast cells by pressurized carbon dioxide. *Biotechnol Prog* 7:201-204
- Lin HM, Chen LF (1994) Method for recovery of intracellular material by disruption of microbial cells with carbon dioxide under pressure. US Patent 5,306,637
- Lin HM, Yang Z, Chen LF (1992) An improved method for disruption of microbial cells with pressurized carbon dioxide. *Biotechnol Prog* 8:165-166
- Lin HM, Yang Z, Chen LF (1993) Inactivation of *Leuconostoc dextranicum* with carbon dioxide under pressure. *Chem Eng J* 52:B29-34
- Lozano P, Diego TD, Sauer T et al (2007) On the importance of the supporting material for activity of immobilized *Candida antarctica* lipase in ionic liquid/hexane and ionic liquid-supercritical carbon dioxide biphasic media. *J Supercrit Fluids* 40:93-100
- Lozano P, Villora G, Gomez D et al (2004) Membrane reactor with immobilized *Candida antarctica* lipase B for ester synthesis in supercritical carbon dioxide. *J Supercrit Fluids* 29:121-128
- Mackey BM, Forestiere K, Isaacs N (1995) Factors affecting the resistance of *Listeria monocytogenes* to high hydrostatic pressure. *Food Biotechnol* 9:1-11
- Marr R, Gamse T (2000) Use of supercritical fluids for different processes including new developments: a review. *Chem Eng Proc* 39:19-28
- Mesiano AJ, Beckman EJ, Russell AJ (1999) Supercritical biocatalysis. *Chem Rev* 99:623-633
- Mizuno T, Goto M, Kodama A et al (2000) Supercritical water oxidation of a model municipal solid waste. *Ind Eng Chem Res* 39:2807-2810
- Mortazavi SM, Mohammadabadi MR, Khosravi-Darani K et al (2007) Preparation of liposomal gene therapy vectors by a scalable method without using volatile solvents or detergents. *J Biotechnol* 129:604-613
- Mosqueira FG, Higgins JJ, Dunnill P et al (1981) Characteristics of mechanically disrupted bakers' yeast in relation to its separation in industrial centrifuges. *Biotechnol Bioeng* 23:335-343
- Mozafari MR, Khosravi-Darani K (2007) An overview of liposome-derived nanocarrier technologies, pp.113-123. In: Mozafari MR (ed) *Nanomaterials and Nanosystems for Biomedical Applications*. Springer, Netherlands
- Mozhaev VV, Heremans K, Frank J et al (1994) Exploiting the effects of high hydrostatic pressure in biotechnological applications. *Trend Biotechnol* 12:493-501
- Mozhaev VV, Lange R, Kudryashova EV et al (1996) Application of high hydrostatic pressure for increasing activity and stability of enzymes. *Biotechnol Bioeng* 52:320-331
- Nakamura K (1990) Biochemical reactions in supercritical fluids. *Trend Biotechnol* 8:288-292
- Nakamura K, Enomoto A, Fukushima H et al (1994) Disruption of microbial cells by the discharge of high pressure carbon dioxide. *Biosci Biotechnol Biochem* 58:1297-1301
- Nivens DE, Applegate BM (1996) Method for nucleic acid isolation using supercritical fluids, US Patent 5,922,536
- Noel Marie OM, Athes V, Combes D (2000) Combined effects of pressure and temperature on enzyme stability. *High Pres Res* 19:317-322
- Reverchon E (1999) Supercritical anti-solvent precipitation of micro and nanoparticles. *J Supercrit Fluids* 15:1-21
- Romero MD, Calvo L, Alba C et al (2005) Enzymatic synthesis of isoamyl acetate with immobilized *Candida antarctica* lipase in supercritical carbon dioxide. *J Supercrit Fluids* 33:77-84
- Saddler JN (1992) Biotechnology for the conversion of lignocellulosics. *Biomass Bioenergy* 2:229-238
- Sanagi MM, Hung WP, Yasir SM (1997) Supercritical fluid extraction of pyrazines in roasted cocoa beans effect of pod storage period. *J Chrom A* 785:361-367
- Saykhedkar SS, Singhal RS (2004) Supercritical-carbon dioxide extraction of griseofulvin from the solid matrix obtained after solid-state fermentation. *Biotechnol Prog* 20:818-824
- Schutte H, Kroner KH, Hustedt H et al (1983) Experiences with a 20 liter industrial bead mill for the disruption of microorganisms. *Enz Microb Technol* 5:143-148
- Shishikura A, Takahashi H, Hirohama S et al (1992) Citric acid purification process using compressed carbon dioxides. *J Supercrit Fluids* 5:303-312
- Spilimbergo S, Bertucco A, Lauro FM et al (2003) Inactivation of *Bacillus subtilis* spores by supercritical CO₂ treatment. *Inn Food Sci Emerg Technol* 4:161-165
- Srinivasan G, Elliott JR (1992) Microcellular materials via polymerization in supercritical fluids. *Ind Eng Chem Res* 31:1414-1417
- Steckel H, Thies J, Mueller BW (1997) Micronization of sterols for pulmonary delivery by supercritical carbon dioxide. *Int J Pharm* 152:99-110
- Subramanian B, Rajewski RA, Snavely K (1997) Pharmaceutical processing with supercritical carbon dioxide. *J Pharm Sci* 86:885-890
- Tamer IM, Chisti Y, Moo-Young M (1998) Disruption of *Alcaligenes latus* for recovery of poly(hydroxybutyric acid): comparison of high-pressure homogenization, bead milling and chemically induced lysis. *Ind Eng Chem Res* 37:1807-1814
- Tomasko L, Chon YH (1997) Gas crystallization of polymer pharmaceutical composite particles. The 4th Int Symp Supercrit Fluids, Sendai, Japan 55-57

- Van-eijs AMM, Wokke JMP, Ten Brink B et al (1983) Downstream processing of fermentation broth with SC carbon dioxide. *Proceed Int Symp Supercrit Fluids* 799-805
- Wells SL, DeSimone J (2001) CO₂ technology platform: an important tools for environmental problem solving. *Ang Chem Int Ed* 40:518-527
- Williams JR, Clifford AA, Al-Saidi SHR (2002) Supercritical fluids and their applications in biotechnology and related areas. *Mol Biotechnol* 22:263-286
- Winters MA, Frankel DZ, Debenedetti PG et al (1999) Protein purification with vapor phase carbon dioxide. *Biotechnol Bioeng* 62:247-258
- Yalpani M (1993) Supercritical fluids: Puissant media for the modification of polymers biopolymers. *Poly* 34:1102-1105
- Yeo S, Debenedetti PG, Sugunakar YP et al (1994) Secondary structure characterization of micro-particulate insulin powders. *J Pharm Sci* 83:1651-1656
- Yeo S, Lim GB, Debenedetti PG et al (1993) Formation of micro-particulate protein powders using a supercritical fluid antisolvent. *Biotechnol Bioeng* 41:341-346
- Yoshimura T, Furutera M, Shimoda M et al (2002a) Inactivation efficiency of enzymes in buffered system by continuous method with microbubbles of supercritical carbon dioxide. *J Food Sci* 67:3227-3231
- Yoshimura T, Shimoda M, Ishikawa H et al (2002b) Effect of CO₂ flow rate on enzyme inactivation by continuous method with microbubbles of supercritical carbon dioxide. *J Fac Agric Kyushu* 46:345-352
- Zagobelny J, Bright FV (1992) In situ studies of protein conformation in supercritical fluids: trypsin in carbon dioxide. *Biotechnol Prog* 8:421-423
- Zheng Y, Tsao GT (1996) Avicel hydrolysis by cellulase enzyme in supercritical CO₂. *Biotechnol Let* 18:451-454